

COMPACTORS

Husqvarna LP 9505

WEIGHT (COMPLETE PRODUCT W/O SIDE PACKED CENTRIFUGAL FORCE ARTICLES)
72 kN

1680 kg

TRENCH COMPACTOR LP 9505 | 850 mm | KUBOTA | ARTICULATED COM

1/8















PRODUCT DESCRIPTION

The highly productive Husqvarna LP 9505 articulated trench compactor delivers a smooth, compacted surface, which doesn't dig up soil when turning. Due to the high operating weight and ultimate traction, it is suitable for all kinds of soils (dry or wet) but especially suited for cohesive materials like clay and silt. The fuel-efficient engine provides class-leading power for a whole day of uninterrupted work and the radio remote control offers great flexibility, better ergonomics and safer working conditions. Servicing is quick and easy with all service points clearly marked and easily accessed under the hoods.

Feature overview (10)

- Flexibility
- Excellent traction
- Easy to operate
- Always ready
- Optimal static compaction
- Serviceability
- ✓ Covered drum ends
- Easy loading and transporting
- Powerful and fuel efficient
- Stable machine

FLEXIBILITY

Radio remote control technology allows the operator to choose the best position of where to stand, providing for better ergonomics and safer working conditions. This lets you focus on the final result.

EXCELLENT TRACTION

High and wide drum pads increase traction on slopes and steep gradients as well as in wet soils.

EASY TO OPERATE

Remote control has a large informative display for guidance and trouble shooting.







Search



All products specification LP 9505	LP 9505 850 mm KUBOTA ARTICULATED COM 967 95 08-01
Engine	
Motor/engine model	D1105
Engine Power (As rated by the engine manufacturer)	18 kW
tarter	Electric
xhaust emissions (CO ₂ EU V)	976 g/kWh
Power source	Diesel
Product data	
Centrifugal force	72 kN
peed	22.5 m/min
limensions	
Product size length	1,856 mm
roduct size width	850 mm
Product size height	1,369 mm
Veight (complete product w/o side packed articles)	1,680 kg
Packaging length	1,950 mm
Packaging width	900 mm
Packaging height	1,585 mm
rticle gross weight	1,750,000 g
ound and noise	
ound power level, guaranteed (LWA)	106 dB(A)
iound pressure level at operators ear (LpA)	83 dB(A)

Showing 21 of 21