

1/1



PRODUCT DESCRIPTION

LF 75 LAT is a fast-operating forward plate compactor, designed for efficient compaction of asphalt and soil. Ideal for repair jobs and maintenance work, such as driveways and parking lots. The large water tank features an oversized cap to enable less frequent and fast refills. It is easy to clean, leaves no marks on the pavement and uses whatever water is available on-site.

Feature overview (6)

- ✓ Hours of efficient work
- Easy handling, excellent results
- More work with less water
- Easy to transport
- Saving storage space
- Optimized for asphalt

HOURS OF EFFICIENT WORK

COMPACTORS

Husqvarna LF 75 LAT

NEW

PLATE WIDTH

420 mm

WEIGHT (COMPLETE PRODUCT W/O SIDE PACKED ARTICLES)

95 kg

CENTRIFUGAL FORCE

15 kN

FORWARD PLATE LF 75 LAT \mid 420mm \mid Honda

Art nr: 967 85 49-05

EASY HANDLING, EXCELLENT RESULTS

The efficient, patented low-vibration handle lowers the vibration levels below 2 m/s², allowing you to work for hours without becoming fatigued or exceeding any regulatory threshold limit values.



The watering system, that prevents the bottom plate from sticking to the hot asphalt, uses only a minimum of water thanks to the easily adjustable water flow.



Search



All products specification LF 75 LAT	LF 75 LAT 420mm Honda 967 85 49-05	LF 75 LAT 500mm Honda 967 85 49-06
Engine		
Motor/engine model	GX160	GX160
Engine Power (As rated by the engine manufacturer)	3.6 kW	3.6 kW
Starter	Recoil	Recoil
Exhaust emissions (CO ₂ EU V)	757 g/kWh	757 g/kWh
Power source	Petrol	Petrol
Product data		
Compaction application	Asphalt and Soil	Asphalt and Soil
Centrifugal force	15 kN	15 kN
Speed	27 m/min	28 m/min
Dimensions		
Plate width	420 mm	500 mm
Product size length	1,037 mm	1,037 mm

Product size width	420 mm	500 mm
Product size height	1,114 mm	1,114 mm
Weight (complete product w/o side packed articles)	95 kg	97 kg
Packaging length	620 mm	860 mm
Packaging width	850 mm	620 mm
Packaging height	840 mm	840 mm
Article gross weight	95,000 g	107,000 g
Sound and noise		
Sound power level, guaranteed (LWA)	105 dB(A)	105 dB(A)
Sound pressure level at operators ear (LpA)	95 dB(A)	91 dB(A)
Vibration		
Vibrations left/front handle	6 m/s ²	6 m/s²
Vibrations right/rear handle	1.2 m/s ²	1.2 m/s ²

Showing 26 of 26

ACCESSORIES









TTACHMENTS
Hock paving
it

ccessory for prward plate compactors,...

Fork lift device

Accessory for Compaction equipment, Fo...

water tanks **Water tank** Transport wheel kit

Accessory for Forward plate compactors,...

× SPAREPARTS





ATTACHMENTS

Block paving kit

ATTACHMENTS

Transport wheel kit

Accessory for

Compaction equipment, Forward pl...

Accessory for

Forward plate compactors, Reversib...