COMPACTORS

Husqvarna LF 60 LAT

NEW



350 mm

WEIGHT (COMPLETE PRODUCT W/O SIDE PACKED ARTICLES)

70.4 kg

CENTRIFUGAL FORCE

10.4 kN

FORWARD PLATE LF 60 LAT | 350 mm | Honda | GX160 Art nr: 967 85 48-04

1/6















PRODUCT DESCRIPTION

LF 60 LAT is a lightweight, fast-operating forward plate compactor, designed for efficient compaction of asphalt and soil. It is ideal for repair jobs and maintenance work such as driveways and parking lots. The large water tank features an oversized cap to enable less frequent and faster refills. The machine is easy to clean, leaves no marks on the pavement and uses whatever water is available on-site.

Feature overview (6)

- Hours of efficient work
- Easy handling, excellent results
- More work with less water
- Easy to transport
- Optimized for asphalt
- Saving storage space

HOURS OF EFFICIENT WORK

The efficient, patented low-vibration handle lowers the vibration levels below 2 m/s², allowing you to work for hours without becoming fatigued or exceeding any regulatory threshold limit values.



EASY HANDLING, EXCELLENT RESULTS

The watering system, that prevents the bottom plate from sticking to the hot asphalt, uses only a minimum of water thanks to the easily adjustable water flow.



MORE WORK WITH LESS WATER

The large corrosion-free water tank and smart water distribution system enable you to work longer with less stops for re-filling.



Search



All products specification LF 60 LAT	LF 60 LAT 350 mm Honda GX160 967 85 48-04
Engine	
Motor/engine model	GX160
Engine Power (As rated by the engine manufacturer)	3.6 kW
Power/fuel type	Petrol
Starter	Recoil
Exhaust emissions (CO ₂ EU V)	757 g/kWh
Power source	Petrol
Product data	
Compaction application	Asphalt and Soil
Centrifugal force	10.4 kN
Speed	22 m/min
Dimensions	
Plate width	350 mm
Product size length	1,014 mm
Product size width	350 mm
Product size height	961 mm
Weight (complete product w/o side packed articles)	70.4 kg
Packaging length	620 mm
Packaging width	850 mm
Packaging height	840 mm
Article gross weight	87,000 g
Sound and noise	
Sound power level, guaranteed (LWA)	102 dB(A)

Sound pressure level at operators ear (LpA)	87 dB(A)
Vibration	
Vibrations left/front handle	8 m/s²
Vibrations right/rear handle	2 m/s²

Showing 27 of 27

ACCESSORIES









TTACHMENTS lock paving it

ocessory for orward plate compactors,...

ATTACHMENTS **Transport** wheel kit

Accessory for Forward plate compactors,...



SERVICE KITS/TOOLS Service kit LF 50/60

Accessory for Compaction equipment, Fo...

SPAREPARTS



ATTACHMENTS **Block paving kit**

Accessory for Forward plate compactors, Rever...