COMPACTORS

# Husqvarna LT 6005


PLATE WIDTH 230 mm

WEIGHT (COMPLETE PRODUCT W/O SIDE PACKED ARTICLES)

68 kg

68

RAMMER LT 6005 | 9" | Honda | 230 mm



















#### PRODUCT DESCRIPTION

LT 6005 is a well-balanced and powerful rammer, developed for efficient compaction of granular and cohesive soils such as clay and silt. Ideal for compaction in trenches or other narrow spaces, for example around pillars and pipes. Equipped with the latest Honda GXR120 engine, which is especially designed for rammers. The rammer offers superb control, low noise and low emissions.

Feature overview (4)

- High compaction performance
- Great ergonomics
- Easy to manoeuvre
- Easy to service

# HIGH COMPACTION PERFORMANCE

Efficient compaction thanks to a powerful Honda engine mounted in a compact, durable chassis delivering high speed and high impact force.



#### **GREAT ERGONOMICS**

The single lifting point and rollers on the steering bow make on-site handling easy. Transport wheel kit available as an accessory.



## **EASY TO MANOEUVRE**

The three-position throttle control (idle, full speed, stop/closed) also closes the fuel line to prevent leakage. The balanced design provides excellent traction and maneuverability.



## Search



All products specification LT 6005	LT 6005   9"   Honda   230 mm 967 85 45-04	LT 6005   11"   Honda   280 mm 967 85 45-05
Engine		
Motor/engine model	GXR 120	GXR 120
Engine Power (As rated by the engine manufacturer)	2.7 kW	2.7 kW
Power/fuel type	Petrol	Petrol
Exhaust emissions (CO <sub>2</sub> EU V)	674 g/kWh	674 g/kWh
Power source	Petrol	Petrol
Product data		
Speed	16.5 m/min	16.5 m/min
Dimensions		
Plate width	230 mm	280 mm
Product size length	726 mm	726 mm
Product size width	345 mm	345 mm
Product size height	1,084 mm	1,084 mm
Weight (complete product w/o side packed articles)	68 kg	69 kg
Packaging length	1,100 mm	1,100 mm
Packaging width	450 mm	450 mm
Packaging height	970 mm	970 mm
Article gross weight	79,500 g	84,000 g
Sound and noise		
Sound power level, guaranteed (LWA)	106 dB(A)	106 dB(A)
Sound pressure level at operators ear (LpA)	92 dB(A)	92 dB(A)

Showing 21 of 21

#### **ACCESSORIES**





ERVICE ITS/TOOLS ervice kit F 5005/6005

occessory for ompaction equipment, Fo...

ATTACHMENTS
Transport
wheel kit

Accessory for Compaction equipment, T...